



US008373975B2

(12) **United States Patent**
Liang et al.

(10) **Patent No.:** **US 8,373,975 B2**
(45) **Date of Patent:** **Feb. 12, 2013**

(54) **PROTECTIVE COVER, KEY ASSEMBLY
USING THE SAME AND PORTABLE
ELECTRONIC DEVICE USING THE KEY
ASSEMBLY**

(75) Inventors: **Shi-Xu Liang**, Shenzhen (CN); **Jun-Lin
Chen**, Shenzhen (CN); **Yung-Chang
Yen**, Taipei Hsien (TW)

(73) Assignees: **Shenzhen Futaihong Precision
Industry Co., Ltd.**, Shenzhen (CN);
FIH (Hong Kong) Limited, Kowloon
(HK)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 229 days.

(21) Appl. No.: **12/884,227**

(22) Filed: **Sep. 17, 2010**

(65) **Prior Publication Data**
US 2011/0228493 A1 Sep. 22, 2011

(30) **Foreign Application Priority Data**
Mar. 16, 2010 (CN) 2010 1 0124904

(51) **Int. Cl.**
G06F 1/16 (2006.01)
H05K 5/00 (2006.01)
H04M 1/00 (2006.01)
H04M 9/00 (2006.01)
H04B 1/08 (2006.01)
H01H 3/12 (2006.01)
H01H 13/14 (2006.01)
(52) **U.S. Cl.** **361/679.02**; 361/679.56; 455/575.8;
455/550.1; 455/347

(58) **Field of Classification Search** 361/728,
361/729, 730, 732, 736, 752, 807, 809, 810,
361/837, 679.56; 200/293, 318, 329, 339,
200/318.1, 318.2, 5 R, 275, 296, 302.3, 320,
200/330, 341–345, 517, 520, 536, 547, 550,
200/553; 455/575.1, 575.2, 575.3, 575.8,
455/550.1, 347; 379/422
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,148,183	A *	11/2000	Higdon et al.	455/575.1
7,595,712	B2 *	9/2009	Nishino et al.	335/207
8,089,772	B2 *	1/2012	Chen	361/752
2009/0159416	A1 *	6/2009	Tseng et al.	200/341
2011/0226599	A1 *	9/2011	Xiao	200/341

* cited by examiner

Primary Examiner — Zachary M Pape

Assistant Examiner — Binh Tran

(74) *Attorney, Agent, or Firm* — Altis Law Group, Inc.

(57) **ABSTRACT**

A protective cover includes a cover body and a pressing body integrally mounted to the cover body. The cover body has an accommodating cavity recessed from a surface of the cover body and an accommodating hole defined through the base wall of the accommodating cavity. The pressing body is mounted to the cover body and includes a pressing portion and a resisting post. The pressing portion is configured for being received within the accommodating cavity and exposed from the accommodating hole. The resisting post protruding from a surface of the pressing portion away from the cover body corresponding to the switch. There also discloses a key assembly using the protective cover and a portable electronic device using the key assembly.

11 Claims, 5 Drawing Sheets

